

Specifications

SPECIFICATIONS		L5040
ENGINE		Diesel, 4-cylinder, water cooled, 8-valve, turbocharged, mechanical indirect injection
Power output	KM	50.86
Total displacement	cm ³	2434
PTO power	KM	44.6
Max torque	Nm	164,2 (1400-1800)
Fuel tank capacity	L	54

TRANSMISSION

Transmission type		Mechanically engaged 4x4
Total number of speeds		F16/R16
Max speed / min.	km/h	30,3 / 0,2 (depending on tire size)
Gearbox		4 speed
Reduction box		Four speed, creep gear w standardzie
Shuttle		Mechanical, quick change of driving directon with a lever on a steering column
Main clutch		Dry, one stage
Brakes		Hydraulic wet, disc brakes
Differential lock (Front / Rear)		N/A / mechanical differential lock

PTO

PTO speeds		540 / 540E - selected with an external lever
PTO clutch		Independent, multidisc, wet, hydraulically operated

HYDRAULICS

Hydraulic pump capacity	L/min	35.6
3-point linkage category		I
3-point linkage control		Mechanical: position control
Lifting capacity	kg	1750
External hydraulic outlets (pairs)		2

DIMENSIONS AND WEIGHT

Total length / height / width	mm	3245 / 2550 (ROPS) / 1470 (min. thread)
Wheelbase		1915
Thread	Front	mm 1135
	Rear	mm 1125, 1225, 1325
Standard tire size		Front: 9,5-16; Rear: 13,6-28
Turning radius	m	3,2 (with braking)
Tractor weight in standard spec.	kg	1730

FURTHER FURTHER STANDARD FEATURES

Power steering, two external hydraulic sections, drawbar